



## Salgrave, engraving laminate

### PRODUCT INFORMATION

RIGID PRESSED PVC SHEET

Product: **SALGRAVE ENGRAVE**

Type of film	: Pressed, rigid PVC sheet for engraving		
Product Ref.	: ENGRAVE		
Emboss	: polished / polished ; polished / matt ; polished / satin		
Colours	: Various		
Thickness	: 1.50 mm		
Width	: 800 mm	alternatively	1,250 mm
Length	: 1,700 mm		2,460 mm

#### 1. TECHNICAL DATA \*

	Standard	Units	Nom.
1.1 Specific gravity	: DIN 53479	[ g/cm <sup>2</sup> ]	1.396
1.2 Hardness Shore A	: DIN EN ISO 868		75
1.3 Tensile strength	: DIN EN ISO 527-3	[ Mpa ]	54
1.4 Elongation at break	: DIN EN ISO 527-3	[ % ]	50-100
1.5 Tear strength	: DIN 53356	[ Mpa ]	61
1.8 Shrinkage	: BS 3757	[ % ]	<2
1.9 VICAT softening	: DIN EN ISO 306 / A50	[° C]	81.5
2.0 Max. service temp.	:	[° C]	60
2.1 Flammability	: DIN 75200	mm / min	0 (self-extinguishing)

\* All tests carried out on 1.50 mm gauge material. The above values are typical properties and not specifications. The values may vary with gauge.

This information about Salgrave, engraving laminate products is based on our current understanding. Our products are sold under the condition that the customer takes responsibility for checking that the product is suitable for the intended application. The technical data are provided in accordance with the respective standard indicated. Any publication of this information even in extract form is only permissible by agreement with us.